



Mod. **ATLAS/P**

**TRINCIA PIEGHEVOLE - BROYEUR PLIABLE - FOLDING SHREDDER
KLAPPBARE HÄCKSLER - TRITURADORA PLEGABLE
СКЛАДНЫЕ ИЗМЕЛЬЧИТЕЛЬ**



**Trincia pieghevole per aree verdi, cover crops e paglia.
Per trattori da 100 a 200 HP**



**Broyeur pliable pour espaces verts, couvert végétal et paille.
Pour tracteurs de 100 à 200 CV.**



**Folding shredder for grasslands, cover crops and straw.
For 100-200 HP tractors**



**Klappbare Häcksler für Grünland, cover crops und Stroh.
Für Traktoren von 100 bis 200 PS**



**Trituradora plegable para cubiertas vegetales, cover crops y paja.
Para tractores de 100 a 200 CV.**



Складные измельчители для тракторов от 100 до 200 л.с.



Mod. ATLAS/P



100-200 HP




ATLAS/P	Scales icon		Roller dimensions diagram (A, B)				Roller detail diagram		Tractor icon		PTO icon	
	Kg.	LBS	A mm.	B mm.	A inches	B inches	mm.	inches	N.	HP	PTO	N.
4000/P	1580	3483	4086	4488	160,87	176,69	2200	86,61	44	100-200	1000	5+5
5000/P	1830	4034	4986	5388	196,30	212,12	2200	86,61	52	100-200	1000	5+5
6000/P	2090	4607	6066	6468	238,82	254,65	2200	86,61	64	100-200	1000	5+5

* Peso con rullo * Poids avec rouleau * Weight with roller * Gewicht mit Walze * Peso con rodillo * Вес с каток



- 4 ruote sterzanti posteriori regolabili (tipo 8.00/15 - 5 fori) oppure rullo posteriore Ø mm 194
- 4 roues arrières réglables (mod. 8.00/15 - 5 trous) ou alors rouleau arrière Ø mm 194
- 4 rear adjustable steering wheels (mod. 8.00/15 - 5 holes or rear roller Ø mm 194)
- Martelli e controcoltello + perni filettati con dado
- Marteaux et contre couteau + axes filetés avec écrou
- Hammers and counterblade + axles with nut
- Gancio di sicurezza automatico
- Crochet de sécurité automatique
- Automatic safety hook
- 4 hintere verstellbare Steuerräder (Mod. 8.00/15 - 5 Löcher) oder hinterer Walze Ø mm 194
- 4 ruedas terciantes posteriores regulables (tipo 8.00/15 - 5 gurejos) o rodillo trasero Ø mm 194
- 4 регулируемые задние колеса рулевого управления (тип 8.00/15 - 5 отверстий) или же задним роликом Ø мм 194
- Hämmer und Gegenmesser + Gewindebolzen mit Muttern
- Martillos contracuchilla + pernos rosado con tuercas
- Молотки и контролезвие + тыри с резьбой с гайкой
- Automatischer Sicherheitshacken
- Enganche de seguridad automático
- Автоматический предохранительный крюк



ATLAS/P:

A Ø mm 452 **A** Ø inches 17,80
B Ø mm 193,7 x 10 **B** Ø inches 7,62 x 0,39
C n. 5+5 **C** n. 5+5

OPZIONE OPTION OPTION OPTION OPCIÓN ОПЦИЯ



- Trincino idraulico anteriore
- Broyeur "satellite" hydraulique frontal
- Front hydraulic grass cutting disk
- Vorderer Mittelschneider mit hydraulischem Antrieb
- Cortador hidráulico frontal
- Фронт гидравлический измельчитель



Via Proventa, 41
 48018 Faenza (Italia)
 Tel. +39 0546 29050
 Fax +39 0546 663986

www.falc.eu | info@falc.eu